



ECS 500 (35 bar) Fluoro-K Clean Agent

ECS 500 (35 bar) Fluoro-K Fire Extinguishing Agent

Fire Extinguishing System

Optimize cylinder storage location for flexible and cost-effective installation

The Kidde 35 bar Clean Agent Suppression System using Fluoro-K provides superior performance compared to standard 25 bar systems. The higher storage pressure of 35 bar enables improvement of agent travel distance for applications where ADS™ performance levels are not required. Now you have the flexibility of a mid-tier solution to meet application size, design requirements and the client's budget.

System Benefits:

The system provides all the benefits of the standard 25 bar system with added advantages that provide improved system design flexibility and reduced installation and material costs:

- Including new 180L. cylinder size with 50mm valve reduces cylinder quantities and installation time required,
- Increased system pressure allows for longer pipe runs and use of smaller pipe diameters
- Provides flexibility to remotely locate cylinder storage area more than twice the distance from the hazard area when compared to 25 bar systems

System Features:

- A wide range of cylinder sizes.
- Provides economical protection of multiple enclosures when used with directional valves



Why Choose the 35 bar Clean Agent System with Fluoro-K?

Rapid-Response. In seconds, the System discharges the extinguishing agent into the hazard area resulting in less damage, fewer repair costs and reduced downtime compared to a standard code-compliant sprinkler system.

Minimizes Damage. Removed from the hazard area by ventilation, the agent allows a virtually immediate return to “business as usual” without the interruption of a costly clean-up and the expense of damage to assets from residue.

People-Safe. The agent is non-toxic, when used in compliance with National Standards, and does not impair breathing or obscure vision in an emergency situation, providing an added measure of safety for personnel.

Environmentally-Responsible. With a zero Ozone Depletion Potential, a low atmospheric lifetime, and its rapid suppression performance, the agent not only offers low environmental impact, but reduces the potentially devastating atmospheric pollutants of an uncontrolled fire.

Laboratory-Tested. Kidde Fluoro-K has been tested and found to be effective on a wide range of Class A surface (wood, paper and cloth), Class B (flammable liquids) fires.

Globally-Accepted. Kidde Fluoro-K agent meets the standards of Underwriters Laboratories, FM Approvals, the National Fire Protection Standard NFPA-2001, and the U.S. EPA SNAP program.

Kidde Stamp of Approval. Kidde quality engineers and chemical experts working alongside third party laboratories have subjected the FK-5-1-12 agent to rigorous testing prior to acceptance – so you can be assured of receiving the same high-quality fire suppression delivery system platforms that we have shipped to you in years past and that you expect to receive from us going forward.

Typical Applications Protected by an Kidde Clean Agent System:

- Bank Vaults
- Battery Backup Rooms
- Clean Manufacturing Facilities
- Data Processing Centers
- Document Storage
- Process Control Rooms
- Simulators

Integrated Clean Agent System Components:

- Extinguishing Control Panel
- Suppression Cylinders
- Notification Devices

Fluoro-K Component Approvals & Listings:

- UL Listed
- FM Approved



Kidde-Fenwal, LLC
400 Main Street
Ashland, MA 01721, USA

KFI U.K. Limited
Station Road,
Bentham, Lancaster, LA2 7NA

Kiddel Technologies
Survey No. 28/2, 44/2 and 45
Rasyani, Dandapta Road
Raigad Maharashtra-410207, India

www.kiddefenwal.com | 508.881.2000

Kidde Fire Systems, Kidde Fire Protection and Fenwal Controls branded products are created exclusively by Kidde-Fenwal, LLC.
All other trademarks are the property of their respective owners.
©2026 Kidde-Fenwal, LLC | All Rights Reserved.

 **KiddeFenwal**
SS K-114 -UK